

## WW UL94V-0 Compliant

### Wirewounds Offer Wide Range of Power Ratings and Tolerances

**RALEIGH, NC** (Jan. 8, 2019) – The WW Series high temperature silicone coated wirewound resistors meet UL94V-0 flammability requirements. The all welded WW is available in power ratings from 0.5W up to 11W and tolerances from 5% to 0.1%. Typical TCR for the WW series ranges from 90 ppm/°C or better for resistance values below 1 ohm to 20 ppm/°C or better for values above 10 ohms. The WW is available in low inductance and non-inductive styles as well as high pulse power handling and high voltage versions. This versatility makes the WW a popular choice for a wide range of power management applications, motor controls and protection, and power supply input protection for a variety of electronic equipment.



Pricing for the WW depends on size, resistance value, and tolerance. Contact Stackpole or one of our franchised distributor partners for volume pricing.



For more information about Stackpole products, contact Stackpole Electronics, Inc. at 3110 Edwards Mill Road, Suite 207, Raleigh, NC 27612; phone 919-850-9500; email [marketing@seielect.com](mailto:marketing@seielect.com); or visit the website at [www.seielect.com](http://www.seielect.com).

Stackpole Electronics Inc. is a leading global manufacturer of resistors supplying to the world's largest OEMs, contract manufacturers and distributors. Headquartered in Raleigh, N.C., the privately held company began manufacturing in 1928 as part of Stackpole Carbon Company in St. Mary's, Pennsylvania. Now part of the Akahane Stackpole Manufacturing Group (ASMG), Stackpole has manufacturing facilities in Japan, Taiwan, China and Mexico; warehousing facilities in El Paso, Shenzhen and Japan; and international sales offices in Tokyo, Taipei, London, Hong Kong and Shenzhen.